

MPP on the sea bed, a Technical but also Operational challenge to undertake


Brown Field Application on TOTAL operated Block 17, offshore Angola



Speakers : Pierre-Jean BIBET (Total E&P)
: François-Xavier PASQUET (Total E&P Angola)
Co-author : Fabien PAPOT (Total E&P Angola)




GirRI: a Brownfield project offshore Angola



GirRI: a bold multiphase pumping challenge

2 World Firsts

- High Boost MPP
- Integrated Power Management Systems



A Technical Challenge...

- ❖ Need for “one pump fits all branches”, wide range of operating points

	Flowrate (Am ³ /h)	GVF (% Avol)	ΔP (bar)
Operating range needed	200 - 550	10 - 60	15 - 105
Final characteristics	100 - 750	0 - 100	5 - 130

- ❖ High ΔP demand: 130 bar
- ❖ High shaft power requirement: 2.5 MW per MPP unit.
- ❖ World first MPP High boost application (ΔP record with 88.9 bar @ 25%GVF field proven in 05/2016 on P80L MPP).



First main technical challenge was to use a brand new technology from R&D.


Risk mitigation by 1) creating a robust MPP system

- ❖ Power and speed margins.
- ❖ Increased robustness of the pump.



Coating on pump hydraulic stages

- ❖ Increased robustness of the pumping station.



Pump Station architecture

Risks mitigation by 2) Going through extensive FAT & SIT programs



System Integration Test



Slug Tests


...But also an Operational challenge

- ❖ MPP impacts both upstream and downstream flow regimes.
- ❖ Operators have a very good experience with their wells. However the MPP modifies the dynamic of the whole multiphase production system.
- ❖ Trade off must be found between pushing the MPP speed, choking the wells, rerouting the wells, producing with a higher suction pressure to get a more stable and at longer term a better production.

Start-up and operation of such powerful MPP equipment change many of Operators practices and ways of thinking.




Key difference between a typical Pump and a MPP



*With a MPP, the operating limits are function of the GVF and fluid densities
 ➔ Operating envelope is changing in real-time.*

Same MPP on 2 very different configurations :

Very different Multiphase Flow Dynamic systems



Multiphase Flow Production System Characteristics

❖ **Flow at inlet is independent from flow at the outlet of the pump.** System is composed of

- Upstream : wells & flowline.
- Downstream : riser & gas lift (process topside can also impact MPP).
 - High inertia and limited control.

❖ Wells & flowline

- Gas fraction in flowrate can reach ups and downs **very quickly** (0-100%)
 - Slug flow conditions with high variations in flowrate.
- Wells **very sensitive** to backpressure variations (highest impact of MPP is on P80).

❖ Riser & gas lift

- **Pump needs to create ΔP to enter operating envelope :**
 - suction pressure to be quickly reduced after start-up (valid for P70 only).
 - rapid effect of gas lift on discharge P (valid for P70 as P80 is far from wells).
 - Location of P80 reduces slugging, enhances stability but raises impact of start-up on wells (drawdown limit).



A system approach is mandatory


Main key parameters to manage a successful start-up

❖ Before start-up

- Ramp-down the wells to reach a minimum stable flow.
→ Higher flowrate would require more ΔP to enter operating envelope.
- Reducing gas lift allows to have margin to play on ΔP during critical phases (if operating point too close from mini-flow trip limit).
- Closing riser head choke is efficient to increase ΔP at riser base but disturbs the system at reopening (very sensitive on P70 branch).
- At restart, MPP is speed controlled to enter into the operating envelope.

❖ During start-up

- Wells are then reopened to gain ΔP & flow, with draw down control.
- Recycle line is used also to get higher ΔP and stabilize the system.
- Increase/reduction of gas lift allows to reduce/increase ΔP (quick effects on P70).



Takeaway Points

- ❖ MPP on the sea bed is a **Technical** but also an **Operational** challenge to take up.
- ❖ Two aspects of the equipment must be equally treated: 1) to Integrate the Equipment, 2) to Operate it.
- ❖ Operating successfully a production line with a MPP requires major changes in Operating procedures.
- ❖ During the start-up phase, the teams faced more complex flow assurance challenges than anticipated by all studies undertaken and by the Operators training system scenarios.
- ❖ Close cooperation between project, commissioning, start-up & operations teams allowed various successful optimizations to maximize MPPs availability and efficiency in restarts.

Key lesson learnt:

A successful transition to a production phase with continuous MPP boosting requires strong collaboration between all teams, Technical knowledge and a whole Subsea System approach.



Thank you for your attention !



DISCLAIMER and COPYRIGHT RESERVATION

The TOTAL GROUP is defined as TOTAL S.A. and its affiliates and shall include the person and the entity making the presentation.

Disclaimer

This presentation may include forward-looking statements within the meaning of the Private Securities Litigation Reform Act of 1995 with respect to the financial condition, results of operations, business, strategy and plans of TOTAL GROUP that are subject to risk factors and uncertainties caused by changes in, without limitation, technological development and innovation, supply sources, legal framework, market conditions, political or economic events.

TOTAL GROUP does not assume any obligation to update publicly any forward-looking statement, whether as a result of new information, future events or otherwise. Further information on factors which could affect the company's financial results is provided in documents filed by TOTAL GROUP with the French *Autorité des Marchés Financiers* and the US Securities and Exchange Commission.

Accordingly, no reliance may be placed on the accuracy or correctness of any such statements.

Copyright

All rights are reserved and all material in this presentation may not be reproduced without the express written permission of the TOTAL GROUP.

